


# High temperature resistant ties

Collars & cable ties



**One-use product :** Yes

**Material :** PA6,6

**Total length :** De 98 à 200 mm

**Widht :** 2,5 - 3,6 - 4,8 mm

**Closure type :** Progressive tightening

**Ex stock :** Yes

**Standard packaging :** 100 pcs bags

**MOQ for stock product :** 1.000 pcs

**Customs tariff :** 39 23 90 90

**Possible Marking :** Yes

**Delivery Deadline :** 4 semaines

**Available colors :**



These ties are high temperature-proof, between 125 and 145°C, on short periods

Dimensions (mm)	Min. locking diameter	Max. locking diameter	Tensile strength	Qty per carton (minimum and to be ordered by)
2.5 x 98	1 mm	21 mm	80 N	40.000 pcs
3.6 x 140	2 mm	35 mm	130 N	25.000 pcs
3.6 x 200	2 mm	50 mm	130 N	20.000 pcs
4.8 x 200	2 mm	50 mm	220 N	13.000 pcs
4.8 x 290	2.5 mm	79 mm	220 N	10.000 pcs
7.8 x 365	8 mm	100 mm	540 N	3.500 pcs

They comply with UL94V2 fire norms. To tighten better, use a PSP8 tool.

They are available in black or frosted, in 4 to 6 weeks.

Free samples on request

